

Herramientas hidráulicas para compresión de terminales / *Hydraulic crimping tools*

**HT-240U**



**Tipo de compresión / Compression type:**  
Hexagonal.

**Rango compresión / Compression range:**  
Terminales / Lugs: 10 - 240 mm<sup>2</sup>  
Uniones / Splices: 10 - 150 mm<sup>2</sup>

**Fuerza / Output:**  
6 tn.

**Peso / Weight:**  
2,2 kg.

**Largo / Length:**  
400 mm.

**Matriz de aplicación / Compression die:**  
R19.

Herramienta hidráulica monocomando para compresión hexagonal de terminales y uniones de cobre y aluminio. Su cabezal en U facilita la extracción frontal de las matrices intercambiables con total comodidad. Posee bomba de doble acción y válvula de corte automático con gatillo de alivio. Liviana y versátil, permite un cómodo y práctico manipuleo en sitios con poco espacio.

**Incluye matrices de compresión de 10 - 240 mm<sup>2</sup>.**

*Single body hydraulic tool, for performing hexagonal crimps on copper and aluminum lugs and splices. U-shaped head ensures fast and comfortable die extraction and replacement. Two speed pump rapidly advances the ram to contact the connector, automatically switching over to lower handle force for crimping. Automatic pressure release valve, with manual retraction trigger. Lightweight and versatile, this tool allows comfortable operation in restricted spaces.*

*Includes compression dies (10 - 240 mm<sup>2</sup>).*